























Versatile and modular, It is available in 3 different versions (standalone, counter top or wall mounted); it is proposed either in a 15" landscape mode or in a 21" landscape or portrait configuration.

KRYSTAL can be associated with a wide range of options, suiting a number of applications.

Simple and elegant, its slim, vertical design will be a real asset for the digitalisation of sales and service areas.

KRYSTAL integrates the YUNO Kiosk touch technology (in 15 or 21" - see above), an ODP 444 ticket printer, a payment terminal and a 2D barcode

This kiosk will meet the needs of various customer journeys, from booking to order taking, including Click & Collect, queue management and appointment taking.











TOUCH THE DIFFERENCE

KRYSTAL

Standalone, counter top or wall mount versions available

Portrait or landscape mode (YUNO Klosk 21") Landscape mode (YUNO Klosk 15")

Projected capacitive panel (PCAP) - multi-touch 10 points

Choice of 3 processors: i5, i3 or 3965U

M2 128 GB

Integrated payment terminal: modular adapter plate for the integration of a wide range of handsets

ODP 444 80 mm thermal printer

1D/2D barcode reader











| SYSTEM | YUNO KIOSK 15 OR 21" | |
|--------------|---|--|
| Processors | Kaby Lake - i5-7300U / i3-7100U / Celeron 3965U | |
| Memory | DDR4 - 4 GB (standard) up to 32 GB | |
| M2 | 128 GB (2 slots) | |
| LCD | 15 and 21" | |
| Touch screen | Edgeless PCAP panel (multi-touch 10 points) | |
| | | |

| α TII | FB C | $\mathbf{v} \boldsymbol{\epsilon} \boldsymbol{\tau}$ | |
|--------------|------|--|------|
| OTH | ER 3 | | EWIS |
| | | | |
| | | | |

| Printer | ODP 444 thermal printer |
|---------|-------------------------|
| Scanner | 1D/2D (DATALOGIC) |

| /(|) | PO |) F | ET. | S |
|----|---|----|-----|-----|---|
| | | | | | |

| Serial ports | 4 x serial ports (+ 5/12 V power supply for COM3 / COM4) |
|--------------|--|
| USB | 4 x USB 2.0 + 2 USB 3.0 |
| LAN | 10/100/1000 Base-T |

EFT

| PAX | S300 / Q25 / A35 |
|----------|---------------------------------|
| Verifone | P400 / VX820 |
| Ingenico | LANE 5000 / LANE 3000 / IPP 350 |

DIMENSIONS & WEIGHT

| Counter top / Wall-mount configuration | Standalone configuration (stand + ground plate) |
|--|---|
| 73 cm | 143 cm |
| 43 cm (screen + payment terminal) | 55 cm (ground plate) |
| 26 cm | 55 cm (ground plate) |
| 19 kg | 51 kg (stand + ground plate: 32 kg) |
| | configuration 73 cm 43 cm (screen + payment terminal) 26 cm |

MISCELLANEOUS

| CEM | CE Directive CEM 2014/30/EU (Class B) |
|--------------------------|---|
| Security | CE Directive BT 2014/35/EU |
| Operating temperature | 5 - 35° C |
| Front side | Water and dust resistant (IP 54) |
| Wall-mount configuration | specific additional rear mounting cover |
| Colour(s) | grey/black (other colours upon request – for specific orders) |
| Compatible OS | Windows 10 IoT Enterprise, Linux |







