

- ALL-IN-ONE
- MOBILITY
- MODULAR
- PANELS PC
- PRINTERS
- DISPLAYS
- ACCESSORIES

OLC TOUCH 10.1

Additional touch-screen for POS, Retail and Kiosk / OEM applications



Improved Customer Relationship Management

The OLC Touch 10.1 has been designed for interactive digital display applications at check-outs, enabling various contents (promotional or advertising videos, images, text and multimedia contents, loyalty programs, special contests and customer-consumer surveys, etc...) to be broadcast and proposed at the POS, in a "touch" version.

This second adjustable, standalone 10.1-inch touch screen in wide format (16:9 with 5 points PCAP Technology) is the perfect dual-screen additional equipment to entertain queuing customers, build loyalty campaigns and run promotional or advertising messages; it allows effective and real-time interactive information and communication to customers at retail outlets, leisure and sport venues, museums, bars, restaurants and hotels, etc.

A single USB cable provides all necessary connections (video, power supply, touch function), which is a clear advantage at the POS counter; same with the VESA options which enable wall mount and vertical applications in addition to the standalone version, which can be very useful in specific OEM integration and Kiosk environments.

The OLC Touch 10.1 is available in black or white and can be integrated at the back of AURES YUNO EPOS system (Dual screen Touch system).



OLC TOUCH 10.1



MODEL OLC TOUCH 10.1

Main chip	Display link DL - 4110 (N)
Touch screen	10.1" 16:9 touch panel (PCAP Technology)
Resolution	1024 x 600
Brightness	350 cd/m ²
Viewing angle	(left, right, top, bottom) 80° / 80° / 80° / 80°
Tilt angle	0 - 80°

CONNECTIONS

1 single USB cable	180 cm (power, video, touch screen)
--------------------	-------------------------------------

ENVIRONNEMENT

EMC & Safety	CE, FCC Class A, LVD
Operating temperature	0 ~ 40°C
Storage temperature	-20 ~ 70°C
Humidity level (while operating)	20% to 85% RH - condensation-free
Humidity level (storage)	20% to 85% RH - condensation-free
Dimensions	260 (L) x 200 (H) x 155 (D) (in mm)
Weight	2.1 kg (net)
Brackets	VESA 75 x 75 mm
Options	Stand-alone version (external device, connected to any EPOS) Dual screen version (integrated to the YUNO system) Pole version (thanks to the VESA fixings)
Colours	Black or White

Specifications are subject to change without notice - © AURES 2024